



## INTERSECTION GUIDANCE DISPLAY

The Intersection Guidance Display is used in the Identipark parking guidance system to indicate the availability of parking spaces within a certain lane or lanes associated with the display. The display comprises a set of three arrows of green LEDs – LEFT, STRAIGHT and RIGHT - and a single cross of red LEDs. The arrows are used to indicate the direction in which there are available spaces by illuminating one of the arrows or any combination thereof. The cross is used to indicate that all bays in the associated area are full.

### TECHNICAL DATA

#### Input Bus

Identipark Sensor Bus, from the IntelliBooster  
DC Power and Multi-drop RS485 communications  
May be powered from mains

#### LED Indications

Direction indicated by:  
Green arrows for vacant spaces  
Red cross for full spaces.

#### Power Supply

(Standard and HD) 28 to 56V DC (Bus supplied)  
(Enhanced) 32 to 56V DC (Bus Supplied)

#### Dimensions

322mm x 32mm x 66mm (l x w x h)

#### Mounting

U-shaped mounting bracket for ceiling or wall mount

#### Material

Mild Steel, powder coated

**Operating  
Temperature**

-30°C to +80°C

**Storage Temperature**

-40°C to +85°C

**Humidity**

Up to 98% non-condensing

**EMC**

As per ETS 3001-489/EN 50293

**Safety**

Complies with UL/CSA-60950, EN60950 and IEC60950

**Housing**

IP54 rating